



PRO/pak

PRO/PAK 1.5" F ANGLED COUPLING

UM12-NF

12 GPM @ 100 PSI ENGLISH TEXT

\$775.00 Guaranteed US Price

FEATURES

PRO/pak includes 2.7 ft. (82.3cm) hose, 3 nozzles and shoulder strap. L 14.25" x W 11" x H 18" (36.2 x 27.9 x 45.7cm)

SPECIFICATIONS

Expansion	Multi
Flow Rate	12 gpm
Inlet Coupling Style	Rocker
Inlet Coupling Swivel	Non-Full Time Swivel
Pressure	100 psi (7 bar)
Valve Actuation Method	Rotational
Valve Design	Aluminum Slide Valve

DOCUMENTS

Online Videos

[FOAM OVERVIEW VIDEO \(MP4\)](#)

[PRO/PAK SERIES VIDEO](#)

Instructions For Installation, Safe Operation and Maintenance

[PRO/PAK INSTRUCTION MANUAL \(PDF\)](#)

[Z PORTUGUESE PRO/PAK SISTEMA DE ESPUMA \(PDF\)](#)

[Z SPANISH SISTEMA DE ESPUMA MULTI – PROPÓSITO PORTÁTIL PRO/P \(PDF\)](#)

Certifications & Approvals

[ISO 9001:2015 CERTIFICATION \(PDF\)](#)

[PRO/PAK CCCF CERTIFICATION \(PDF\)](#)

Technical Specifications and Drawings

[UM12-NF ITEM SPECIFICATION \(DOC\)](#)

ABOUT THE PRO/PAK

The PRO/pak foam injection and application system is the ideal choice to apply any Class A, AFFF or Alcohol Resistant foam concentrate fast, and easy. Everything you need is contained in one unit that attaches to the end of your 1" or 1½" (25 or 38 mm) hose line. The PRO/pak is a 2.5 gal. (9.5 l) foam reservoir with a built-in eductor that can be set to the ratio of foam or wetting agents being used with three different quick connect nozzles included, the PRO/pak system is capable of producing low or medium expansion finished foam, while operating at wide range of low or high inlet pressures.