



THUNDERFOG Series

THUNDERFOG W/GRIP 2.5\"/>

JTS250PS

95-250 GPM @ 100 PSI SPINNING TEETH

\$1200.00 List Price

FEATURES

Selectable gallonage nozzle with five flow settings of 95, 125, 150, 200, and 250 gpm @ 100 psi (360-470-570-750-950 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Uniquely cut fixed fog teeth or optional stainless steel spinning teeth. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. 2.5\"/>

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	95/125/150/200/250gpm
Inlet Coupling Style	Rocker
Body Size	2.5\"/>
Inlet Coupling Swivel	Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Spinning
Operating Pressure	100 psi (7 bar)
Remote Control	No

DOCUMENTS

Certifications & Approvals

[ISO 9001:2015 CERTIFICATION \(PDF\)](#)

[THUNDERFOG FM APPROVAL \(PDF\)](#)

[THUNDERFOG NFPA 1964 \(PDF\)](#)

Service Procedures

[THUNDERFOG SERVICE PROCEDURE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG INSTRUCTION MANUAL \(PDF\)](#)

[Z PORTUGUESE MANUAL DE INSTRUÇÕES THUNDERFOG & QUADRAFOG \(PDF\)](#)

Product Brochures

[Z INDONESIAN THUNDERFOG \(PDF\)](#)

Technical Specifications and Drawings

[JTS250PS FINISHED GOOD PRINT \(PDF\)](#)

[JTS250PS FINISHED GOOD PRINT - STEP \(DXF\)](#)

[JTS250PS ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[THUNDERFOG SERIES VIDEO \(MP4\)](#)

ABOUT THE THUNDERFOG SERIES

A selectable gpm nozzle that is available in two basic series: the 200 series, with a selectable flow range of 30-200 gpm (110-750 l/min), or 95-250gpm (360-950 l/min) and the 250 series, with a selectable flow range of 95-250 gpm (360-950 l/min). The 200 series is an excellent choice for 1.5\", 1.75\", or 2.0\"/>