



QUADRAFOG Series

QUADRAFOG W/GRIP 1.5\"F

FQS125PS

30-125 GPM @ 100 PSI SPINNING TEETH

\$935.00 List Price

FEATURES

Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110-230-360-470 l/min @ 7bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5\" NH swivel is standard.

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	30/60/95/125gpm (110/230/360/470 l/min)
Inlet Coupling Style	Rocker
Body Size	1.5\" (38 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Spinning
Operating Pressure	100 psi (7 bar)
Remote Control	No

DOCUMENTS

Certifications & Approvals

[1.5IN QUADRAFOG/QUADRACUP NFPA 1964 \(PDF\)](#)

[ISO 9001:2015 CERTIFICATION \(PDF\)](#)

[QUADRAFOG FM APPROVAL \(PDF\)](#)

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

[1.5\" QUADRAFOG & QUADRACUP SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z INDONESIAN QUADRAFOG \(PDF\)](#)

Technical Specifications and Drawings

[FQS125PS FINISHED GOOD PRINT \(PDF\)](#)

[FQS125PS FINISHED GOOD PRINT \(ZIP\)](#)

[FQS125PS FINISHED GOOD PRINT - STEP \(DXF\)](#)

[FQS125PS ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

ABOUT THE QUADRAFOG SERIES

An excellent selectable gallonage nozzle for any 1\" (25mm) or 1.5\" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1\" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5\" version has a range of 30-125 gpm (110-470 l/min), and is available in high(100 psi) or low-pressure(75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.